

WAX-BASED FINISHES
Natural Finishing

Translucent wood-tone finish
HOLZWACHS LASUR 3IN1 - Oil-Wax Based - Interior and Exterior

For cladding, roofing, window and fences

Holzwachs Lasur is a satin, impregnating self-sealing 3-in-1 finish, for interiors and exteriors, with a natural oil, wax and resin base. It can be diluted with products from the Solvoil range, penetrating the wood to create a decorative, protective and highly elastic layer on the surface. Water repellent and breathable, it does not flake. It contains UV filters and additives for wood protection. Application of two or three coats is recommended. To renew the coating, simply apply a coat on the dry and clean surface. There is no need to sand.



Recommendations for application:
Holzwachs Lasur 3IN1 creates a natural, satin effect. For a more decorative effect and greater protection, one or two coats of Weather Oil UV can be applied on it.

Customizable with Borma Colour System

Code	Desc.	Pack.
3320XX-3X1	750 ml	06 pcs.
3322XX-3X1	2,5 Lt	02 pcs.
3330XX-3X1	5 Lt	02 pcs.
3344XX-3X1	10 Lt	
3340XX-3X1	20 Lt	

Translucent Wood-Tone Finish
NATURAQUA HOLZWACHS LASUR 3IN1 - Oil-Wax Based Finish - Interior and exterior

For cladding, roofing, window and fences

A waterbased acrylic, waxy impregnating self-sealing 3-in-1 finish for interiors and exteriors. Odourless and dilutable in water it enhances the grain of the wood using natural and bright colours for deep penetration of the wood. Water repellent and breathable it protects the wood from atmospheric agents. Added UV filters impart light-stability and special additives protect the wood against harmful biological agents. Application of two or three coats is recommended.



Recommendations for application:
The colours of Naturaqua Holzwachs Lasur 3IN1 are brighter than the same Holzwachs Lasur 3IN1 oil-wax base. The level of protection offered by the two products is very similar, however the water-based version needs intermediate sanding between the coats and restoration phase.

Customizable with Borma Colour System

Code	Desc.	Pack.
NAT3305XX-3X1	375 ml	06 pcs.
NAT3315XX-3X1	750 ml	06 pcs.
NAT3325XX-3X1	2,5 Lt	02 pcs.
NAT3335XX-3X1	10 Lt	
NAT3345XX-3X1	20 Lt	

High Solid, Deep Penetrating Waxed Impregnating Agent
HOLZWACHS LASUR HD50

A blend of natural oils, waxes and resins formulated for coating indoor / outdoor wood paneling. Self-sealing, it provides colour and long-lasting protection due to deep penetration of the wood fibres and high solid content, applied in two or three coats. Also suitable for metallic decorative effects.



Recommendations for application:
HD50 is characterised by an extremely easy application thanks to its high viscosity and excellent brushability. Very easy maintenance (no sanding required).

Customizable with Borma Colour System

Code	Desc.	Pack.
3320XX-HD	750 ml	06 pcs.
3322XX-HD	2,5 Lt	02 pcs.
3330XX-HD	5 Lt	02 pcs.
3344XX-HD	10 Lt	
3340XX-HD	20 Lt	